

ENGINE SPEED:	1500	FUEL:	LOW ENERGY
COMPRESSION RATIO:	9.7:1	FUEL SYSTEM:	LPG IMPCO
JACKET WATER - MAX. OUTLET (°C):	99		
COOLING SYSTEM:	JW+OC	FUEL PRESS. RANGE (KPAg):	10.0 - 34.5
IGNITION SYSTEM:	CDIS	THC:FREE INERT RATIO	1.9
EXHAUST MANIFOLD:	WC	RATED ALTITUDE (m):	153
COMBUSTION:	STANDARD	AT AIR TO TURBO. TEMP. (°C):	25
		EXHAUST O2 EMISSION LEVEL:	2.0 %O2
		FUEL LHV (MJ/Nm3):	23.3
		APPLICATION:	50 Hz GENSET

RATING AND EFFICIENCY		NOTES	LOAD	100%	75%	50%
ENGINE POWER	(WITHOUT FAN)	(1)	KW	183	137	92
GENERATOR POWER	(WITHOUT FAN)	(2)	EKW	172	129	86
ENGINE EFFICIENCY	(ISO 3046/1)	(3)	%	28.9	26.2	24.0
ENGINE EFFICIENCY	(NOMINAL)	(3)	%	28.9	26.2	24.0
THERMAL EFFICIENCY	(NOMINAL)	(4)	%	62.0	64.8	67.1
TOTAL EFFICIENCY	(NOMINAL)	(5)	%	90.9	91.1	91.1

ENGINE DATA						
FUEL CONSUMPTION	(ISO 3046/1)	(6)	MJ/bkW-hr	12.46	13.72	15.03
FUEL CONSUMPTION	(NOMINAL)	(6)	MJ/bkW-hr	12.46	13.72	15.03
AIR FLOW (0 °C, 101.3 kPa)		(7)	Nm3/bkW-hr	3.54	3.79	4.25
AIR FLOW		(7)	kg/bkW-hr	4.58	4.9	5.49
INLET MAN. PRESSURE		(8)	KPAa	84	70	57
INLET MAN. TEMPERATURE	(MEASURED IN PLENUM)	(9)	°C	42	46	50
TIMING		(10)	°BTDC	34	34	34
EXHAUST STACK TEMPERATURE		(11)	°C	562	554	547
EXHAUST GAS FLOW (0 °C, 101.3 kPa)		(12)	Nm3/bkW-hr	3.9	4.18	4.68
EXHAUST MASS FLOW		(12)	kg/bkW-hr	5.18	5.56	6.22

EMISSIONS DATA						
NOx (as NO2) (corr. 5% O2)		(13)	mg/Nm3 (dry)	7051	6881	6710
CO (corr. 5% O2)		(14)	mg/Nm3 (dry)	1740	1646	1536
THC (corr. 5% O2), molecular weight of 15.84)		(14)	mg/Nm3 (dry)	886	816	743
NMHC (corr. 5% O2, molecular weight of 15.84)		(14)	mg/Nm3 (dry)	133	123	112
EXHAUST O2		(15)	% DRY	2.0	2.1	2.2
LAMBDA				1.06	1.03	1.06

HEAT BALANCE DATA						
LHV INPUT		(16)	KW	634	523	382
HEAT REJECTION TO JACKET (JW)		(17) (21)	KW	222	200	153
HEAT REJECTION TO ATMOSPHERE		(18)	KW	25	21	15
HEAT REJECTION TO LUBE OIL (OC)		(19) (21)	KW	35	32	24
HEAT REJECTION TO EXHAUST (LHV to 25°C)		(20)	KW	168	134	98
HEAT REJECTION TO EXHAUST (LHV to 120°C)		(20)	KW	136	108	79

CONDITIONS AND DEFINITIONS

ENGINE RATING OBTAINED AND PRESENTED IN ACCORDANCE WITH ISO 3046/1 (STD. REF. CONDITIONS OF 25°C, 100 KPA BAROMETRIC PRESSURE, 152 m ALTITUDE). NO OVERLOAD PERMITTED AT RATING SHOWN. CONSULT ALTITUDE CHARTS FOR APPLICATIONS ABOVE MAXIMUM RATED ALTITUDE AND/OR TEMPERATURE.

EMISSION LEVELS ARE BASED ON THE ENGINE OPERATING AT STEADY STATE CONDITIONS. EMISSION TOLERANCES SPECIFIED ARE DEPENDANT UPON FUEL QUALITY. METHANE NUMBER CANNOT VARY MORE THAN ± 3. PUBLISHED PART LOAD DATA MAY REQUIRE ENGINE ADJUSTMENT.

ENGINE RATING IS WITH 1 ENGINE DRIVEN JACKET WATER PUMP.

FOR NOTES INFORMATION CONSULT PAGE THREE.

FUEL USAGE GUIDE

THC:FREE INERT RATIO	<1.0	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	>2.0
IGNITION TIMING	-	-	34	34	34	34	34	34	34	34	34	34
DERATION FACTOR	0	0	0.78	0.82	0.86	0.90	0.93	0.95	0.97	0.99	1.00	1.00

ALTITUDE DERATION FACTORS

AIR TO TURBO (°C)	50	0.94	0.91	0.88	0.86	0.83	0.80	0.78	0.75	0.73	0.71	0.68	0.66	0.64
	45	0.95	0.93	0.90	0.87	0.84	0.82	0.79	0.77	0.74	0.72	0.69	0.67	0.65
	40	0.97	0.94	0.91	0.88	0.86	0.83	0.80	0.78	0.75	0.73	0.71	0.68	0.66
	35	0.99	0.96	0.93	0.90	0.87	0.84	0.82	0.79	0.77	0.74	0.72	0.69	0.67
	30	1.00	0.97	0.94	0.91	0.88	0.86	0.83	0.80	0.78	0.75	0.73	0.71	0.68
	25	1.00	0.99	0.96	0.93	0.90	0.87	0.84	0.82	0.79	0.77	0.74	0.72	0.69
	20	1.00	1.00	0.97	0.94	0.92	0.89	0.86	0.83	0.80	0.78	0.75	0.73	0.71
	15	1.00	1.00	0.99	0.96	0.93	0.90	0.87	0.85	0.82	0.79	0.77	0.74	0.72
	10	1.00	1.00	1.00	0.98	0.95	0.92	0.89	0.86	0.83	0.81	0.78	0.76	0.73
			0	250	500	750	1000	1250	1500	1750	2000	2250	2500	2750

ALTITUDE (METERS ABOVE SEA LEVEL)

FREE FIELD MECHANICAL & EXHAUST NOISE

100% Load Data			dB(A)		(dB)							
Free Field Mechanical	DISTANCE FROM THE ENGINE (METERS)	1	96.3	90.3	85.3	86.3	88.3	92.3	91.3	85.3	74.2	
		7	86.3	83.5	80.5	78.5	77.5	82.5	81.5	73.5	63.4	
		15	80.3	78.4	78.4	76.4	75.4	76.4	73.4	69.4	57.4	
Free Field Exhaust	DISTANCE FROM THE ENGINE (METERS)	1.5	119.6	127.3	113.3	113.8	109.8	113.8	114.3	110.8	109.8	
		7	106.2	116.4	101.9	97.9	95.9	98.4	99.4	100.9	96.9	
		15	99.6	99.0	90.5	91.5	90.5	92.5	93.0	94.0	90.5	
Overall SPL			63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz		

Octave Band Center Frequency (OBCF)

FUEL USAGE GUIDE:

This table shows the derate factor required for a given fuel. Note that deration occurs as the THC:Free Inert ratio decreases.

This Fuel Usage Guide is intended for digester/biogas applications only. Standard rating is based on digester fuel with 130 MN and 1.9:1 THC:Free Inert Ratio.

ALTITUDE DERATION FACTORS:

This table shows the deration required for various air inlet temperatures and altitudes. Use this information along with the fuel usage guide chart to help determine actual engine power for your site.

ACTUAL ENGINE RATING:

To determine the actual rating of the engine at site conditions, one must consider limitations due to fuel characteristics and air system limitations. The Fuel Usage Guide deration establishes fuel limitations. The Altitude/Temperature and RPC (reference Caterpillar Methane Program) are added together to establish air system limitations.

Determine the actual site power available with the following equation:

$$\text{Spec Sheet Power} * (1 - ((1 - \text{FUG deration}) + (1 - \text{Altitude Deration Factor})))$$

Note: Spec sheet rating is based on digester fuel with 130 MN, 96 RPC and 1.9:1 THC:Free Inert ratio.

SOUND DATA:

Data determined by methods similar to ISO Standard DIS-8528-10. Accuracy Grade 3. SPL = Sound Pressure Level.

NOTES

- 1 ENGINE RATING IS WITH 1 ENGINE DRIVEN JACKET WATER PUMP. TOLERANCE IS $\pm 3\%$ OF FULL LOAD.
- 2 GENERATOR POWER DETERMINED WITH AN ASSUMED GENERATOR EFFICIENCY OF 93.8% AND POWER FACTOR OF 0.8 [GENERATOR POWER = ENGINE POWER \times GENERATOR EFFICIENCY].
- 3 ISO 3046/1 ENGINE EFFICIENCY TOLERANCE IS (+)0, (-)5% OF FULL LOAD % EFFICIENCY VALUE. NOMINAL ENGINE EFFICIENCY TOLERANCE IS $\pm 5\%$ OF FULL LOAD % EFFICIENCY VALUE.
- 4 THERMAL EFFICIENCY: JACKET HEAT + LUBE OIL HEAT + EXH. HEAT TO 120°C.
- 5 TOTAL EFFICIENCY = ENGINE EFF. + THERMAL EFF. TOLERANCE IS $\pm 10\%$ OF FULL LOAD DATA.
- 6 ISO 3046/1 FUEL CONSUMPTION TOLERANCE IS (+)5, (-)0% OF FULL LOAD DATA. NOMINAL FUEL CONSUMPTION TOLERANCE IS $\pm 5\%$ OF FULL LOAD DATA.
- 7 UNDRIED AIR. FLOW TOLERANCE IS $\pm 5\%$
- 8 INLET MANIFOLD PRESSURE TOLERANCE IS $\pm 5\%$
- 9 INLET MANIFOLD TEMPERATURE TOLERANCE IS $\pm 5^{\circ}\text{C}$.
- 10 TIMING INDICATED IS FOR USE WITH THE MINIMUM FUEL METHANE NUMBER SPECIFIED. CONSULT THE APPROPRIATE FUEL USAGE GUIDE FOR TIMING AT OTHER METHANE NUMBERS.
- 11 EXHAUST STACK TEMPERATURE TOLERANCE IS (+)35°C, (-)30°C.
- 12 WET EXHAUST. FLOW TOLERANCE IS $\pm 6\%$
- 13 NOX VALUES ARE "NOT TO EXCEED".
- 14 CO, CO₂, THC, and NMHC VALUES ARE "NOT TO EXCEED".
- 15 O₂% TOLERANCE IS ± 0.5 .
- 16 LHV INPUT TOLERANCE IS $\pm 5\%$.
- 17 HEAT REJECTION TO JACKET TOLERANCE IS $\pm 10\%$ OF FULL LOAD DATA, BASED ON TREATED WATER.
- 18 HEAT REJECTION TO ATMOSPHERE TOLERANCE IS $\pm 50\%$ OF FULL LOAD DATA, BASED ON TREATED WATER.
- 19 HEAT REJECTION OF LUBE OIL TOLERANCE IS $\pm 20\%$ OF FULL LOAD DATA, BASED ON TREATED WATER.
- 20 HEAT REJECTION TO EXHAUST TOLERANCE IS $\pm 10\%$ OF FULL LOAD DATA, BASED ON TREATED WATER.

SITE SPECIFIC COOLING SYSTEM SIZING EQUATIONS (WITH TOLERANCES)

- 21 TOTAL JACKET CIRCUIT (JW+OC) = (JW \times 1.1) + (OC \times 1.2).